



J1-LED

URBAN pVMS TRAILER

Options To Customer Include

- CCTV cameras - fixed or PTZ
- Anti-theft DVR cameras & recorders
- Bluetooth for travel time
- Setup lighting
- Spare wheel carrier
- STREAMS colour integration for journey/travel time
- Radar detection kits
- Lock kits & anti-graffiti options



T : +61 7 3807 6272 W : www.j1led.com
A : 10 Production Street Beenleigh QLD 4207

J1-LED

URBAN pVMS Trailer

COMPLIANCE

AS4192:2006
AS1170.2-2009
ADR - Small Trailers

KEY FEATURES

J1's Portable Arrow Board trailers are utilised for traffic management in all forms of infrastructure and construction. The arrow boards are rated for use in Wind Region C (without additional ballast) and comply with Australian Standard AS 4192:2006.

The Portable Arrow Boards feature a newly re-designed trailer and hydraulic lifting mechanism. These features ensure rapid and safe single person deployment. Left arrow, right arrow, double arrow and non-directional warning with switchable rear lamps.

SPECIFICATIONS

C Size

Model No	JL-D-0038
ENCLOSURE SIZE (mm) W x H	2400 x 1190
LANTERN SIZE (mm)	17 x 130
NET WEIGHT (kg)	900
TOWING SIZE (mm) W x H x L	1955 x 2438 x 3760
SETUP SIZE (mm) W x H x L	3147 x 3515 x 3469
DIMMING LEVELS	16
MARINE GRADE ALUMINIUM ENCLOSURE	✓
INGRESS PROTECTION	IP65
VIEWING DISTANCE	≤ 860m @ 110kph
PIXEL CONFIGURATION	592nm amber led
POWER SUPPLY	12vDC, 145w SOLAR, STAND ALONE, 1 SOLAR PANEL
OPERATING TEMPERATURE	-10°C to +70°C
COMMUNICATIONS	STAND-ALONE REMOTE 4G, REMOTE 4G MANAGED SERVER
SETUP MECHANISMS	HYDRAULIC RAM FOR SIGN LIFT
CONTROL SYSTEMS	ONSITE OR REMOTE LOCAL LAPTOP, ITS HOST



T : +61 7 3807 6272 W : www.j1led.com
A : 10 Production Street Beenleigh QLD 4207

